

Results of Rising-Head Permeability Tests					
Borehole ID	Screened Interval (ft)	Screen Length, (ft)	Soil Type(s)	Permeability, K	
				(ft/sec)	(cm/s)
BH-05	55 to 74	19	Colma Sand	1.64E-04	5.00E-03
FV-07	61.5 to 80	19	Colma Sand	3.55E-05	1.08E-03
B-4-6	27 to 42	15	Colma Sand, some Hard Clay	1.84E-05	5.61E-04
B-4-12	25 to 45	20	Colma Sand	3.09E-05	9.41E-04
B-4-15	17 to 37	20	Colma Sand	1.94E-05	5.90E-04
B-4-16	15 to 35	20	Colma Sand	2.49E-05	7.60E-04
B-4-17	9.5 to 19.5	10	Colam Sand	5.19E-05	1.58E-03
B-4-21	15 to 25	10	Colma Sand	6.80E-05	2.07E-03
B-4-24	15 to 25	10	Colma Sand	6.34E-05	1.93E-03
B-4-25	15 to 25	10	Colma Sand, Hard Clay	2.77E-06	8.44E-05
				7.22E-06	2.20E-04
<b>Average</b>				<b>4.42E-05</b>	<b>1.35E-03</b>

FIG\_90: In-Situ Permeabilities of Colma Sand from Rising-Head Tests in Standpipe